

# Styleline® FX

LARGEST PRODUCT  
VIEWING AREA IN THE  
**INDUSTRY**



STYLELINE® FX sets a new standard in protection against condensation by providing advanced thermal design fully compliant with DOE 2017 regulations.

Available for cooler and freezer applications, STYLELINE® FX door and frame system is ideal for those high-end applications without sacrificing performance and elegance!

- Elegant edge-to-edge glass appearance
- Proven hardware simplicity and reliability
- Pre-wired energy controller
- STYLELINE LED Plus included

**STYLELINE®**  
By Commercial Refrigerator Door Company





[www.styleline.com](http://www.styleline.com)



# All Glass Appearance Door!




# Styleline® FX

- 
**APPLICATION:** Cooler, High Humidity and Freezer
- 
**PROTECTION:** NT: 75F/75%RH @ 35F Cooler Temp.  
 HH: 75F/85%RH @ 35F Cooler Temp.  
 LT: 75F/64%RH @ -10F Cooler Temp.
- 
**LIGHTING:** Styleline LED Plus
- 
**WARRANTY:** 2-years workmanship and materials, 5-years LED, 10-years non-heated glass pack

- DOE 2017 complaint
- Full length handle standard
- 2 Pane Glass Pack (cooler), Argon filled, Low-E
- 3 Pane Glass Pack (high humidity, freezer), Argon filled, Low-E
- Energy controller standard. Occupancy Sensor for HH & LT
- Advanced thermal glass pack design delivers enhanced condensation protection with very low energy use
- STYLELINE® reliable door hinge, hold open cam, one-time adjustment torque rod and self-closing hinge system
- Stainless steel trim & new and improved magnetic door gasket design

## What's Included:

- STYLELINE® LED Plus lighting system
- Five heavy-duty 27" NSF approved black shelves and post with price tag molding and black brackets. White shelves with galvanized post and galvanized brackets are also available
- Standard STYLELINE® Warranty



Finishes



Full-length Handle



Post Colors

Door Size W x H	24" x 63"	26" x 63"	30" x 63"	26" x 72"	24" x 72"	26" x 80"	30" x 72"	30" x 80"
NCO Height	64 3/4"	64 3/4"	64 3/4"	73 3/4"	73 3/4"	81 5/8"	73 3/4"	81 5/8"
Doors	NCO Width							
1	2' 11/16"	2' 313/16"	2' 73/4"	2' 3 13/16"	2' 11/16"	2' 313/16"	2' 73/4"	2' 73/4"
2	4' 13/16"	4' 65/16"	5' 23/16"	4' 65/16"	4' 13/16"	4' 65/16"	5' 23/16"	5' 23/16"
3	6' 9/16"	6' 813/16"	7' 85/8"	6' 813/16"	6' 9/16"	6' 813/16"	7' 85/8"	7' 85/8"
4	8' 5/16"	8' 115/16"	10' 31/16"	8' 115/16"	8' 5/16"	8' 115/16"	10' 31/16"	10' 31/16"
5	10' 1/16"	11' 113/16"	12' 91/2"	11' 113/16"	10' 1/16"	11' 113/16"	12' 91/2"	12' 91/2"
6	12' 213/16"	13' 75/16"	15' 615/16"	13' 75/16"	12' 213/16"	13' 75/16"	15' 615/16"	15' 615/16"
7	14' 29/16"	15' 913/16"	18' 13/8"	15' 913/16"	14' 29/16"	15' 913/16"	18' 13/8"	18' 13/8"
8	16' 25/16"	18' 5/16"	20' 713/16"	18' 5/16"	16' 25/16"	18' 5/16"	20' 713/16"	20' 713/16"
9	18' 21/16"	20' 213/16"	23' 21/4"	20' 213/16"	18' 21/16"	20' 213/16"	23' 21/4"	23' 21/4"
10	20' 113/16"	22' 55/16"	25' 811/16"	22' 55/16"	20' 113/16"	22' 55/16"	25' 811/16"	25' 811/16"

Complete chart available at [styleline.com](http://styleline.com)

Shelving Size	Description / Information
24" x 27", 26" x 27", 30" x 27"	*Five Standard (black/white) Heavy-Duty epoxy and NSF approved
30" x 36"	*Five Standard Slide Trac™ Gravity-flow (black/white) Heavy-Duty epoxy and NSF approved

Seven shelves with 80" Size Doors

## Options Available:

- Anti-fog film (standard on LT products)
- Slide-Trac® shelving system
- Super Slide-Trac® gravity-flow shelving system
- Satin Silver
- Satin Black